PART NUMBER 2203SP-WHT-ORG

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 22 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 22 (7/30 Bare Copper) INSULATION Low-Smoke PVC .008"

COLOR CODE Black/White/Red

LAY LENGTH 2.5" LHL (approx. 4.8 TPF)

> SHIELD Aluminum Mylar

DRAIN WIRE 24 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket with Orange Stripe

> SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MARKING

> > MADE IN THE USA

OVERALL DIAMETER .134" Nom.

> CABLE WEIGHT 15 Lbs/Mft.

CAPACITANCE 50 pF/ft Nom.

IMPEDANCE 38 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test **FLAME RATING**

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.