PART NUMBER 2203SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789		GL/	
ABLE SPECIFICAT DESCRI		3 Conductor Bare Co	opper, Shielded Plenum	ı, UL Listed	C(UL)US CMF	p	
CONDUCTOR 22 (7/30) Bare Copper)					
INSUL	ATION Low-Sm	Low-Smoke PVC .008"					
COLOR	CODE Black/W	Black/White/Red					
LAY LE	NGTH 2.5" LHI	2.5" LHL (approx. 4.8 TPF)					
s	HIELD Aluminu	m Mylar					
DRAIN	WIRE 24 AWG	24 AWG 7 Strand Tinned Copper					
J	ACKET Low-Sm	Low-Smoke PVC .018"					
JACKET (COLOR White J	White Jacket					
МА		/IRE DEVICE / ZONE I THE USA	A B C D E 0 1 2 3 4	56789	22 AWG C(l	UL)US CMP I	ROHS
OVERALL DIA	METER .134" N	om.					
CABLE W	EIGHT 15 Lbs/	1ft.				R	
CAPACI	TANCE 50 pF/ft	Nom.					
IMPE	DANCE 38 Ohm	5					
TEMPERATURE RA	ATING 0 C to 2	75 C / 300 Volt					

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE T 800.379.1191 windycitywire.com
^{© Windy City Wire, Coble Technology & Products, LLC.}
All rights reserved.