PART NUMBER 2204P-YLW-500

UL Listed and Rated Type CMP Multi-Conductor Non-Shielded Plenum Cable

■ 0275/0725 FT •

SMARTWIRE(TM)

DEVICE/ZONE

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 22 AWG 4 Conductor Bare Copper, Non-Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 22 (7/30 Bare Copper) INSULATION Low-Smoke PVC .008" **COLOR CODE**

LAY LENGTH 2.5" LHL (approx. 4.8 TPF)

Black/White/Red/Green

SHIELD N/A

DRAIN WIRE

N/A **JACKET** Low-Smoke PVC .018"

JACKET COLOR Yellow Jacket

> SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 **MARKING** 22 AWG C(UL)US CMP ROHS

> > MADE IN THE USA

OVERALL DIAMETER .145" Nom.

> CABLE WEIGHT 16 Lbs/Mft.

CAPACITANCE 20 pF/Ft. Nom.

IMPEDANCE 94 Ohms

DC RESISTANCE 16.9 Ohms/Mft. maximum @ 20 C

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.