PART NUMBER 2204SP-BLK

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Pro A/V

■ 0275/0725 FT ● SM	ARTWIRE(TM) PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9	SMARTWIRE GLIDE TECHNOLOGY
CABLE SPECIFICATIONS DESCRIPTION	22 AWG 4 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)	
INSULATION	Low-Smoke PVC .008"	
COLOR CODE	Black/Red/Yellow/Green	
SHIELD	Aluminum Mylar	
DRAIN WIRE	24 AWG 7 Strand Tinned Copper	
JACKET	Low-Smoke PVC .018"	
JACKET COLOR	Black Jacket	
MARKING	SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(THE USA	JL)US CMP ROHS MADE IN
OVERALL DIAMETER	.145" Nom.	
CABLE WEIGHT	19 Lbs/Mft.	
CAPACITANCE	51 pF/Ft. Nom.	R
IMPEDANCE	37 Ohms	
TEMPERATURE RATING	0 C to 75 C / 300 Volt	
INDUSTRY STANDARDS		

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



WINDY CITY

All specifications referenced are nominal measurements unless otherwise noted.

WIRE • T 800.379.1191 • windycitywire.com • [©] WindyCityWire, Cable Technology & Products, LLC. All rights reserved.