PART NUMBER 2204SP-WHT-BRN

ETL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●   SMARTWIRE(TM)   DEVICE/ZONE   A B C D E 0 1 2 3 4 5 6 7 8 9

SMARTWIRE GLIDE® TECHNOLOGY

CABLE SPECIFICATIONS

DESCRIPTION	22 AWG 4 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red/White/Green
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket with Brown Stripe
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.145" Nom.
CABLE WEIGHT	19 Lbs/Mft.
CAPACITANCE	51 pF/Ft. Nom.
IMPEDANCE	37 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA

All specifications referenced are nominal measurements unless otherwise noted.