PART NUMBER 2204SP-WHT-GRN

ETL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT • SMARTWIRE(TM) DEVICE/ZONE





CABLE SPECIFICATIONS

DESCRIPTION 22 AWG 4 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP

CONDUCTOR 22 (7/30 Bare Copper) INSULATION Low-Smoke PVC .008" **COLOR CODE** Black/Red/White/Green

> SHIELD Aluminum Mylar

DRAIN WIRE 24 AWG 7 Strand Tinned Copper

> JACKET Low-Smoke PVC .018"

JACKET COLOR White Jacket with Green Stripe

> SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS **MARKING**

A B C D E 0 1 2 3 4 5 6 7 8 9

MADE IN THE USA

OVERALL DIAMETER .145" Nom.

> CABLE WEIGHT 19 Lbs/Mft.

51 pF/Ft. Nom. CAPACITANCE

IMPEDANCE 37 Ohms

TEMPERATURE RATING 0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA







All specifications referenced are nominal measurements unless otherwise noted.