## PART NUMBER 2204SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ● SMA	RTWIRE(TM) DEVICE/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9
BLE SPECIFICATION	
DESCRIPTIO	
CONDUCTO	
INSULATIO	
COLOR COD	E Black/White/Red/Green
LAY LENGT	H 2.5" LHL (approx. 4.8 TPF)
SHIEL	D Aluminum Mylar
DRAIN WIR	E 24 AWG 7 Strand Tinned Copper
JACKE	T Low-Smoke PVC .018"
JACKET COLO	R White Jacket
MARKIN	G SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETE	<b>R</b> .145" Nom.
CABLE WEIGH	T 19 Lbs/Mft.
CAPACITANC	E 50 pF/ft Nom.
IMPEDANC	E 37 Ohms
DC RESISTANC	E 16.9 Ohms/Mft. maximum @ 20 C
TEMPERATURE RATIN	<b>G</b> 0 C to 75 C / 300 Volt

## **INDUSTRY STANDARDS**

FLAME RATINGApproved For Plenum Use Without Conduit Per NFPA 262 Flame TestAGENCY APPROVALSNEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE T 800.379.1191 windycitywire.com © Windy City Wire, Cable Technology & Products, LIC. All rights reserved.