

PART NUMBER 2206SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	22 AWG 6 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White/Red/Green/Brown/Blue
LAY LENGTH	3" LHL (approx. 4 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.163" Nom.
CABLE WEIGHT	24 Lbs/Mft.
CAPACITANCE	50 pF/ft Nom.
IMPEDANCE	37 Ohms
DC RESISTANCE	16.9 Ohms/Mft. maximum @ 20 C
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHs Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.