PART NUMBER 2212SP-WHT

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6	789	SMARTWIRE GLADE
CABLE SPECIFICAT DESCRI		12 Conductor Para	Connor, Shieldod Dlanum		MD
		G 12 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP 30 Bare Copper)			
		Smoke PVC .008"			
COLOR	COLOR CODE Black/White/Red/Green/Brown/Bl			urple/Gray/Pink/Tan	
LAY LI	ENGTH 4.5" LH	. (approx. 2.8 TPF)			
S	HIELD Aluminu	m Mylar			
DRAIN	I WIRE 24 AWG	7 Strand Tinned Cop	oper		
ſ	ACKET Low-Sm	oke PVC .018"			
JACKET	COLOR White	acket			
MA		VIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4 5 6	789 22 AWG C(U	L)US CMP ROHS
OVERALL DIA	METER .215" N	om.			
CABLE W	EIGHT 43 Lbs/	Aft.			R
CAPACI	TANCE 50 pF/F	Nom.			
IMPE	DANCE 37 Ohm	s			
TEMPERATURE R	ATING 0 C to 7	5 C / 300 Volt			

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

