


PART NUMBER 222PRSP-JCI-BRN

UL Listed and Rated Type CMP Multi-Pair Shielded Plenum Cable

■ 0275/0725 FT ● TEMPERATURE CONTROL SYSTEM SA BUS CABLE A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	22 AWG 2 twisted Pair Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	22 (7/30 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/White, Red/Blue
LAY LENGTH	2" LHL (approx. 6 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Brown Jacket
MARKING	TEMPERATURE CONTROL SYSTEM SA BUS CABLE A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.194" Nom.
CABLE WEIGHT	19 Lbs/Mft.
CAPACITANCE	51 pF/Ft. Nom.
IMPEDANCE	37 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.