


PART NUMBER 241PRS-BAC-ORG

UL Listed and Rated Type CMR Single Pair Shielded Low-Cap Non-Plenum Cable

■ 0275/0725 FT ● TEMPERATURE CONTROL SYSTEM LOW CAP 12.5pF ZONE BUS/COMM LINE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	1 Pair, 24 AWG Tinned Copper Shielded RS-232, RS-422, RS-485 Low-Capacitance Communication, Instrumentation and Special Application Non-Plenum Cable
CONDUCTOR	24 AWG (7/32) Tinned Copper
INSULATION	Foam PE; .017"
COLOR CODE	Black/White
SHIELD	Aluminum Mylar
DRAIN WIRE	24 AWG Stranded Tinned Copper
JACKET	PVC .015"
JACKET COLOR	Orange Jacket
MARKING	TEMPERATURE CONTROL SYSTEM LOW CAP 12.5 PF ZONE BUS / COMM A B C D E 0 1 2 3 4 5 6 7 8 9 24 AWG 2C SHLD (UL) CM C(UL)US 75 C ROHS
OVERALL DIAMETER	.150" Nom.
CABLE WEIGHT	11 Lbs/Mft.
CAPACITANCE	12.5 pF/ft. Nom.
IMPEDANCE	100 Ohms Nom.
TEMPERATURE RATING	75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS UL Subject 444 and NEC Article 800 Type CM Communication Cable, C(UL), RoHS Compliant



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.