


PART NUMBER 242PREPSDB-BAC-BLK

Non-UL Listed Multi-Pair Each Pair Shielded Low-Cap

■ 0275/0725 FT ● DIRECT BURIAL SUNLIGHT RESISTANT 24 AWG 2 PR SHIELDED LOW CAP 12.5 pF



CABLE SPECIFICATIONS

DESCRIPTION	24 AWG 2 Pair Tinned Copper Shielded RS-232, RS-422, RS-485 Low-Capacitance Communication, Instrumentation and Special Application Non-UL Direct Burial Cable
CONDUCTOR	24 AWG (7/32) Tinned Copper
INSULATION	Foam Polyethylene
COLOR CODE	Pair 1: White-Blue/Blue-White Pair 2: White-Orange/Orange-White
SHIELD	FFE Aluminum Polyester
DRAIN WIRE	24 AWG Stranded Tinned Copper
JACKET	Black PE
JACKET COLOR	Black Jacket
MARKING	DIRECT BURIAL SUNLIGHT RESISTANT 24 AWG 2PR SHIELDED LOW CAP 12.5 pF
OVERALL DIAMETER	.197" Nom.
CABLE WEIGHT	20 Lbs/Mft.
CAPACITANCE	12.5 pF/ft. Nom.
IMPEDANCE	100 ohms
TEMPERATURE RATING	-40 to 80 C
VOLTAGE RATING	300 Volts

INDUSTRY STANDARDS

AGENCY APPROVALS Non-UL



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.