## PART NUMBER 243PRPBLU

UL Listed and Rated Type CMP Category 3 Non-Shielded Plenum Cable

■ 0275/0725 FT ● 24	AWG CMP C(UL) IEEE 802.3 10 BASE T CAT 3 ROHS
CABLE SPECIFICATIONS	
DESCRIPTION	24 AWG Category 3 Unshielded Twisted Pair (UTP) Cable for Data Transmissions. This Cable is Plenum Rated and Verified to Category 3 Electricals
CONDUCTOR	24 (Solid Bare Copper)
INSULATION	Plenum PVC .0038"
COLOR CODE	Blue-White/White-Blue Orange-White/White-Orange Green-White/White-Green
JACKET	Plenum PVC
JACKET COLOR	Blue Jacket
MARKING	E106583 (01-12345) 24 AWG CMP C(UL)US IEEE 802.3 10BASE T ETL VERIFIED TO ANSI/TIA-568-C.2 CAT3 RoHS 0/1000
OVERALL DIAMETER	.158" Nom.
CABLE WEIGHT	16 Lbs/Mft.
CAPACITANCE	17.5 pF/Ft. Nom
IMPEDANCE	100 Ohms Nominal
DC RESISTANCE	27 Ohms/Kft
TEMPERATURE RATING	75 C / 300 Volt
VOLTAGE RATING	300 Volts
INDUSTRY STANDARDS FLAME RATING	NFPA 262, Plenum Fire Test (UL 190)
AGENCY APPROVALS	UL Type CMP C(UL)US UL 444, Communications Cables ICEA S-80-576 and NEC Article 800 California State Fire Marshal Approved RoHS Compliant

All specifications referenced are nominal measurements unless otherwise noted.

