PART NUMBER 244PRP-WHT

UL Listed and Rated Type CMP Multi-Pair Non-Shielded Plenum Category 3

■ 0275/0725 FT ● SMAF	TWIRE(TM) MULTI-PAIR TELEPHONE A B C D E 0 1 2 3 4 5 6 7 8 9
ABLE SPECIFICATION	
	Verified To Category 3 Electricals
CONDUCTO	24 (Solid Bare Copper)
INSULATION	Low-Smoke PVC .0069"
	Pair 1: White/Blue, Blue; Pair 2: White/Orange, Orange; Pair 3: White/Green, Green, Pair 4: White/Brown, Brown
SHIELI	N/A
DRAIN WIR	N/A
JACKE	Low-Smoke PVC .014"
JACKET COLOI	K White Jacket
MARKING	24 AWG CMP C(UL)US - IEEE 802.3 10BASE T - ETL VERIFIED TO TIA-568-B.2 CAT 3 RoHS
OVERALL DIAMETE	.157" Nom.
CABLE WEIGH	17 Lbs/Mft.
CAPACITANC	17 pF/ft. Nom.
IMPEDANC	100+/-15% Ohms @ 1 MHz to 16 MHz
TEMPERATURE RATING	0 C to 75 C / 300 Volt
VOLTAGE RATING	300 Volts

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS

UL Subject 444 and NEC Article 800 Type CMP Communication Cable, California State Fire



Marshal Approved, RoHS

All specifications referenced are nominal measurements unless otherwise noted.

