

# PART NUMBER 251357WBT

UL Listed and Rated Type CMR Multi-Pair 1 Pair Shielded, 1 Pair Non-Shielded Non-Plenum Cable

■ 0275/0725 FT ●

SOUND/INTERCOM CABLE

A B C D E 0 1 2 3 4 5 6 7 8 9



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	22 AWG 2 Pair Bare Copper, 1 Pair Shielded, 1 Pair Non-Shielded, Non-Plenum, UL Listed C(UL)US CMR with Water Block Tape
<b>CONDUCTOR</b>	22 (7/30 Bare Copper)
<b>INSULATION</b>	PVC .008"
<b>COLOR CODE</b>	Pair 1: White/Green, Pair 2: Black/Red
<b>SHIELD</b>	Pair 1: N/A, Pair 2: Aluminum Mylar, Overall: Water Block Tape
<b>DRAIN WIRE</b>	Pair 1: N/A, Pair 2: 24 AWG 7 Strand Tinned Copper
<b>JACKET</b>	PVC .025" Nom.
<b>JACKET COLOR</b>	Gray Jacket
<b>MARKING</b>	SOUND / INTERCOM CABLE A B C D E 0 1 2 3 4 5 6 7 8 9 SUITABLE FOR WET LOCATIONS 22 AWG 1P SHIELDED + 22 AWG 1P NO SHIELD C(UL)US CMR 75C ROHS MADE IN THE USA
<b>OVERALL DIAMETER</b>	.208" Nom.
<b>CABLE WEIGHT</b>	23 Lbs/Mft.
<b>CAPACITANCE</b>	OAS: 51 pF/Ft. Nom.; UNS: 20 pF/Ft. Nom.
<b>IMPEDANCE</b>	OAS: 37 Ohms; UNS: 94 Ohms
<b>TEMPERATURE RATING</b>	0 C to 75 C / 300 Volt

## INDUSTRY STANDARDS

**AGENCY APPROVALS** NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.