

PART NUMBER 265000

UL Listed and Rated Type CMP Multi-Pair 1 Pair Shielded Plenum Cable

■ 0275/0725 FT ●

SOUND/INTERCOM CABLE

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

| | |
|---------------------------|---|
| DESCRIPTION | 20 AWG 2 Pair Bare Copper, 1 Pair Shielded Plenum, UL Listed C(UL)US CMP |
| CONDUCTOR | 20 (7 Strand Bare Copper) |
| INSULATION | Low-Smoke PVC .008" Nom. |
| COLOR CODE | Pair 1: Black/Red; Pair 2: White/Green |
| SHIELD | Pair 1: O/A Foil; Pair 2: N/A |
| DRAIN WIRE | Pair 1: 24 AWG Stranded Tinned Copper; Pair 2: N/A |
| JACKET | Low-Smoke PVC .018" Nom. |
| JACKET COLOR | Blue Jacket |
| MARKING | SOUND / INTERCOM CABLE A B C D E 0 1 2 3 4 5 6 7 8 9 20 AWG 1P SHIELED + 20 AWG 1P NO SHIELD C(UL)US CMP ROHS MADE IN THE USA |
| OVERALL DIAMETER | .218" Nom. |
| CABLE WEIGHT | 25 Lbs/Mft. |
| CAPACITANCE | OAS: 60 pF/Ft. Nom.; UNS: 25 pF/Ft. Nom. |
| IMPEDANCE | OAS: 31 Ohms; UNS: 75 Ohms |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

| | |
|-------------------------|---|
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.