PART NUMBER 414400

UL Listed and Rated Type CMR Multi-Conductor Shielded Non-Plenum Cable

■ 0275/0725 FT ● S	MARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5	6789		SMARTWIRE GLADE	
CABLE SPECIFICATIO		5 Conductor twisted	Bare Copper, Shielded	d Non-Plenun	n, UL Listed (C(UL)US CMR	
CONDUC	TOR 18 (7/26	18 (7/26 Bare Copper)					
INSULAT	TON PVC .008	PVC .008"					
COLOR C	ODE Black/Re	Black/Red/White/Green/Brown/Blue					
LAY LEN	GTH 3.75" LH	3.75" LHL (approx. 3.2 TPF)					
SHI	ELD Aluminur	n Mylar					
DRAIN W	/IRE 24 AWG	24 AWG 7 Strand Tinned Copper					
JAC	CKET PVC .018	n					
JACKET CO	LOR Gray Jac	ket					
MARK		IRE DEVICE / ZONE THE USA	A B C D E 0 1 2 3 4 5	678918	AWG C(UL)U	JS CMR 75C ROHS	
OVERALL DIAME	TER .208" No	n.					
CABLE WEI	GHT 47 Lbs/M	ft.				R	
CAPACITA	NCE 68 pF/Ft.	Nom.					
IMPEDA	NCE 28 Ohms						
TEMPERATURE RAT	'ING 0 C to 7	5 C / 300 Volt					

INDUSTRY STANDARDS

AGENCY APPROVALS

NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE · T 800.379.1191 · windycitywire.com · [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.