## PART NUMBER 415100

UL Listed and Rated Type CMR Multi-Conductor Shielded Non-Plenum Cable

■ 0275/0725 FT ● S	MARTWIRE(TM)	DEVICE/ZONE	A B C D E 0 1 2 3 4 5 6	5789	CALIDE STARTWIRE	
CABLE SPECIFICATION DESCRIPT	ION 20 AWG		opper, Shielded Non-Ple	num, UL Listed C(UL	.)US CMR	
CONDUC	ION PVC .008	20 (7/28 Bare Copper) PVC .008"				
COLOR C LAY LEN	<b>GTH</b> 2.75" LH	Black/White 2.75" LHL (approx. 4.3 TPF)				
DRAIN W	VIRE 24 AWG	Aluminum Mylar 24 AWG 7 Strand Tinned Copper				
JACKET CO	,	ket				
MARK OVERALL DIAME	MADE IN	IUSA	A B C D E 0 I 2 3 4 5 6	5789 20 AWG C(1	UL)US CMR 75C ROHS	
CABLE WEI					®	
CAPACITA IMPEDA						
TEMPERATURE RAT	ING 0 C to 7	0 C to 75 C / 300 Volt				

## **INDUSTRY STANDARDS**

AGENCY APPROVALS

NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE · T 800.379.1191 · windycitywire.com · <sup>©</sup> Windy City Wire, Cable Technology & Products, LLC. All rights reserved.