## PART NUMBER 4155105

UL Listed and Rated Type CMRMulti-Pair Each Pair Shielded Non-Plenum Cable

| ■ 0275/0725 FT ● | SMARTWIRE(TM) |   | DEVICE/ZONE                                | ABC     | DE012     | 34567 | 89   |           |       |         |      |
|------------------|---------------|---|--|---------|-----------|-------|------|-----------|-------|---------|------|
|                  |               |   |  |         |           |       |      |           |       |         |      |
| CABLE SPECIFICAT | <b>FIONS</b>  |   |  |         |           |       |      |           |       |         |      |
| DESCRIPTION      |               | 22 AWG 2 twisted Pairs Bare Copper, Individually Shielded Non-Plenum, UL Listed C(UL)US CMR |  |         |           |       |      |           |       |         |      |
| COND             | UCTOR         | 22 AWG(7/   | /30 Bare Copper)                           |         |           |       |      |           |       |         |      |
| INSUL            | ATION         | PVC .008"   |  |         |           |       |      |           |       |         |      |
| COLOR            | R CODE        | Black/Red,  | White/Green                                |         |           |       |      |           |       |         |      |
| LAY LI           | ENGTH         |   | 2" LHL (6 twists pe<br>3" LHL (4 twists pe |         |           |       |      |           |       |         |      |
| S                | HIELD         | Each Pair:  | Aluminum Mylar                             |         |           |       |      |           |       |         |      |
| DRAIN            | I WIRE        | Each Pair: 24 AWG 7 Strand Tinned Copper  |  |         |           |       |      |           |       |         |      |
| J                | ACKET         | PVC .018"   |  |         |           |       |      |           |       |         |      |
| JACKET           | COLOR         | Gray Jack   | et with Violet Stripe                      | 2       | 1.,       |       |      |           |       |         |      |
| MA               | RKING         | SMARTWIE<br>MADE IN   | RE DEVICE / ZONE #<br>THE USA              | A B C D | E 0 1 2 3 | 4567  | 7892 | 22 AWG C( | UL)US | CMR 75C | ROHS |
| OVERALL DIA      | METER         | .175" Nom   |  |         |           |       |      |           |       |         |      |
| CABLE W          | EIGHT         | 19 Lbs/Mft  |  |         |           |       |      |           | R     | )       |      |
| CAPACI           | TANCE         | 50 pF/Ft. N   | Nom.                                       |         |           |       |      |           |       |         |      |
| IMPE             | DANCE         | 38 Ohms   |  |         |           |       |      |           |       |         |      |
| TEMPERATURE R    | ATING         | 0 C to 75   | C / 300 Volt                               |         |           |       |      |           |       |         |      |

## **INDUSTRY STANDARDS**

AGENCY APPROVALS NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE • T 800.379.1191 • windycitywire.com • <sup>© Windy City Wire, Cable Technology & Products, LLC.</sup> All rights reserved.