

PART NUMBER 4160201

UL Listed and Rated Type CMP Multi-Pair Each Pair Shielded Plenum Cable



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 3 Pair Bare Copper, Individually Shielded Plenum, UL Listed C(UL)US CMP
CONDUCTOR	18 (7/26 Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red, White/Green, Brown/Blue
SHIELD	Each Pair: Aluminum Mylar
DRAIN WIRE	Each Pair: 24 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	White Jacket with Red Stripe
MARKING	SMARTWIRE DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.268" Nom.
CABLE WEIGHT	55 Lbs/Mft.
CAPACITANCE	68 pF/Ft. Nom.
IMPEDANCE	28 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE · T 800.379.1191 · windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.