PART NUMBER 5556140

ETL Listed and Rated Type CMP Multi-Pair Non-Shielded Plenum Category 5e Cable

■ 0275/0725 FT •

A B C D E 0 1 2 3 4 5 6 7 8 9





CABLE SPECIFICATIONS

DESCRIPTION 24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable for Data Transmission up to 350 MHz.

This cable is Plenum Rated and Verified to Category 5e Electricals

CONDUCTOR 24 AWG Solid Bare Copper

INSULATION FEP

COLOR CODE White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown

JACKET Low-Smoke PVC

JACKET COLOR Orange Jacket

MARKING * 1000/0000 * A B C D E 0 1 2 3 4 5 6 7 8 9 UTP 4/24 C(ETL)US CMP VERIFIED (ETL) CAT5E

5013896 350 MHZ TIA-568-C.2 WINDY CITY WIRE MADE IN USA

OVERALL DIAMETER .175" Nom.

CABLE WEIGHT 24 Lbs/Mft.

CAPACITANCE 5.6 nF/100 Meters @ 1 kHZ

IMPEDANCE 100 +/- 15 Ohms (0.772-100.0 MHz)

DC RESISTANCE 9.38 Ohms / 100 Meters @ 20 C

TEMPERATURE RATING 60 C / 300 Volt

VOLTAGE RATING 300 Volts

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS ETL Listed Type CMP, Verified to ANSI/TIA 568-C.2 UTP Category 5E



