

PART NUMBER 5556180

ETL Listed and Rated Type CMP Multi-Pair Non-Shielded Plenum Category 5e Cable

■ 0275/0725 FT ●

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

| | |
|---------------------------|--|
| DESCRIPTION | 24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable for Data Transmission up to 350 MHz. This cable is Plenum Rated and Verified to Category 5e Electricals |
| CONDUCTOR | 24 AWG Solid Bare Copper |
| INSULATION | FEP |
| COLOR CODE | White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown |
| JACKET | Low-Smoke PVC |
| JACKET COLOR | Gray Jacket |
| MARKING | * 1000/0000 * A B C D E 0 1 2 3 4 5 6 7 8 9 UTP 4/24 C(ETL)US CMP VERIFIED (ETL) CAT5E 5013896 350 MHZ TIA-568-C.2 WINDY CITY WIRE MADE IN USA |
| OVERALL DIAMETER | .175" Nom. |
| CABLE WEIGHT | 24 Lbs/Mft. |
| CAPACITANCE | 5.6 nF/100 Meters @ 1 kHz |
| IMPEDANCE | 100 +/- 15 Ohms (0.772-100.0 MHz) |
| DC RESISTANCE | 9.38 Ohms / 100 Meters @ 20 C |
| TEMPERATURE RATING | 60 C / 300 Volt |
| VOLTAGE RATING | 300 Volts |
| INDUSTRY STANDARDS | |
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | ETL Listed Type CMP, Verified to ANSI/TIA 568-C.2 UTP Category 5E |



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.