


PART NUMBER 606211

UL Listed and Rated CL2P or CMP

■ 0275/0725 FT ● CLOSED CIRCUIT VIDEO SURVEILLANCE CAMERA CABLE CAMERA/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	Type RG 6/U, Plenum, 18 AWG Solid Bare Copper Center Conductor with a 95% Bare Copper Braid, UL Listed Type CL2P/CMP, C(UL)
CONDUCTOR	18 AWG Solid Bare Copper
SHIELD	95% Bare Copper Braid
JACKET	Plenum Rated PVC
JACKET COLOR	White Jacket
MARKING	CLOSED CIRCUIT VIDEO SURVEILLANCE CAMERA CABLE CAMERA / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 CL2P OR CMP 18 AWG 75 C. (UL) C(UL) FT-6 RG 6/U CCTV
OVERALL DIAMETER	.238" Nom.
CABLE WEIGHT	43 Lbs/M
CAPACITANCE	17.3 pF/ft. Nom.
IMPEDANCE	75 Ohms
TEMPERATURE RATING	75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	Power Limited Circuit Cable, Class 2, UL Type CL2P/CMP, C(UL), RoHS Compliant



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.