

# PART NUMBER 665610-110DB5000

■ 0275/0725 FT ●

A B C D E 0 1 2 3 4 5 6 7 8 9



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable For Data Transmissions up to 100MHz. This Cable is Non-Plenum Rated and Verified to Category 5e Electricals and designed for outdoor use - UV Resistant
<b>CONDUCTOR</b>	24 AWG Solid Bare Copper
<b>INSULATION</b>	PE
<b>COLOR CODE</b>	White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown
<b>JACKET</b>	Polyethelene, Black in color; .240" Nom. Flooding compound under jacket
<b>JACKET COLOR</b>	Black Jacket
<b>MARKING</b>	A B C D E 0 1 2 3 4 5 6 7 8 9 4PR 24 AWG OUTDOOR DIRECT BURIAL CAT 5E
<b>OVERALL DIAMETER</b>	.232" Nom.
<b>CABLE WEIGHT</b>	23 Lbs/Mft.
<b>CAPACITANCE</b>	17 pF/ft MAX.
<b>IMPEDANCE</b>	100 ohms +/-15% (1-100 MHz)
<b>TEMPERATURE RATING</b>	-70 C to +75C / 300 Volt MAX.
<b>VOLTAGE RATING</b>	300 Volts

## INDUSTRY STANDARDS



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.