

PART NUMBER 713110VNQ


UL Listed and Rated Type TC, PLTC, NPLF or FPL Multi-Conductor Shielded Non-Plenum Cable

■ 0275/0725 FT ●

WINDY CITY WIRE

SUN RES

ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION 16 AWG 2 Conductor twisted Bare Copper, Shielded with Water Block Tape and overall jacket. Inner Conductors are Thermoplastic Insulated, Nylon Sheathed, Heat, Oil & Gasoline Resistant 600 Volt TFFN Rated. Material suitable for underground use and indoor trays, "sunlight resistant". (Low voltage industrial process control circuits, Power-Limited circuits, Power-Limited fire alarm circuits, Power-Limited try cable PLTC)

CONDUCTOR 16 (19 Strand Bare Copper)

INSULATION PVC with Nylon

COLOR CODE Black/Red

SHIELD Aluminum Mylar

DRAIN WIRE 22 AWG 7 Strand Tinned Copper

JACKET PVC .040"

JACKET COLOR Black Jacket

MARKING WINDY CITY WIRE A B C D E 0 1 2 3 4 5 6 7 8 9 16AWG (UL) TYPE TC 600V 90C DRY 75C WET "DIR BUR" "SUN RES" PLTC, FPL OR NPLF MADE IN THE USA "SMARTWIRE WATERWARRIOR" ®

OVERALL DIAMETER .280" Nom.

CABLE WEIGHT 49 Lbs/Mft.

CAPACITANCE 50 pF/Ft. Nom.

IMPEDANCE 25 Ohms/Mft.

TEMPERATURE RATING -20 C to 105 C / 600 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS UL Standard 1277, UL 1424 Power limited fire alarm cables, UL 1425 Non-power limited fire alarm cables, UL 13 power limited circuit cables, NEC Articles 340, 725, 760, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.