


PART NUMBER 727400

UL Listed and Rated Type FPLR Multi-Conductor Non-Shielded Non-Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789



SMARTWIRE
GLIDE
TECHNOLOGY

CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 6 Conductor Bare Copper, Twisted, Non-Shielded Non-Plenum Fire Alarm, FPLR (UL)
CONDUCTOR	18 (Solid Bare Copper)
INSULATION	PVC .010"
COLOR CODE	Black/Red/Brown/Blue/Orange/Yellow
SHIELD	N/A
DRAIN WIRE	N/A
JACKET	PVC .018"
JACKET COLOR	Red Jacket
MARKING	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG FPLR (UL) 75C ROHS MADE IN THE USA
OVERALL DIAMETER	.208" Nom.
CABLE WEIGHT	55 Lbs/Mft.
CAPACITANCE	22 pF/Ft. Nom.
IMPEDANCE	86 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS NEC Article 760; FPLR (UL), RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.