


PART NUMBER 7611320

UL Listed and Rated Type FPLP Multi-Conductor Shielded Stranded Plenum Fire Alarm

■ 0275/0725 FT ● FIRE/LIFE SAFETY CONTROL CABLE INIT/IND DEVICE/ZONE ABCDE0123456789



CABLE SPECIFICATIONS

DESCRIPTION	16 AWG 2 Conductor Bare Copper, Twisted, Shielded Stranded Plenum Fire Alarm, FPLP (UL)
CONDUCTOR	16 (19 Strand Bare Copper)
INSULATION	Low-Smoke PVC .008"
COLOR CODE	Black/Red
LAY LENGTH	3.5" LHL (3.4 TPF)
SHIELD	Aluminum Mylar
DRAIN WIRE	22 AWG 7 Strand Tinned Copper
JACKET	Low-Smoke PVC .018"
JACKET COLOR	Red Jacket
MARKING	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 16 AWG FPLP (UL) ROHS MADE IN THE USA
OVERALL DIAMETER	.184" Nom
CABLE WEIGHT	31 Lbs/Mft.
CAPACITANCE	76 Pf/Ft. Nom.
IMPEDANCE	25 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

INDUSTRY STANDARDS

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 760; FPLP (UL), RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.