

# PART NUMBER 761360NYC

UL Listed and Rated Type FPLP Multi-Conductor Non-Shielded Fire Alarm

■ 0275/0725 FT ● 150C. (UL) ALSO CLASSIFIED NYC CERTIFIED SMART STRIP ABCDE0123456789



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	16 AWG 2 Conductor Bare Copper, Non-Shielded Plenum NYC Fire Alarm, FPLP (UL)
<b>CONDUCTOR</b>	16 (Solid Bare Copper)
<b>INSULATION</b>	FEP .015"
<b>COLOR CODE</b>	Black/Red
<b>SHIELD</b>	N/A
<b>DRAIN WIRE</b>	N/A
<b>JACKET</b>	Sole-F PVDF .025"
<b>JACKET COLOR</b>	Red Jacket
<b>MARKING</b>	E143244 16 AWG C(UL)US FPLP 150 C ALSO CLASSIFIED NYC CERTIFIED FIRE ALARM CABLE SMART STRIP
<b>OVERALL DIAMETER</b>	.212" Nom
<b>CABLE WEIGHT</b>	37 Lbs/Mft.
<b>CAPACITANCE</b>	20 pF/Ft.
<b>IMPEDANCE</b>	94 Ohms
<b>TEMPERATURE RATING</b>	OPERATIONAL TEMPERATURE RANGE: -60 C to +150 C

## INDUSTRY STANDARDS

<b>FLAME RATING</b>	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
<b>AGENCY APPROVALS</b>	NEC Article 760; UL Subjects 13, 910, 1424 & 1581, FPLP (UL), Compliant with New York City Local Law 5 requirements



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** · T 800.379.1191 · [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.