


PART NUMBER AXCOMP-BLK

UL Listed and Rated Type CL3P or CMP AMX Axlink Plenum Composite Cable

■ 0275/0725 FT ●

SMARTWIRE(TM) PRO A/V

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	18 AWG 2 Conductor and 22 AWG 1 Pair Shielded with an Overall Plenum Rated Low-Cap PVC Jacket, Plenum Composite Cable UL Type CL3P/CMP
CONDUCTOR	Element 1: 18 AWG 16 Strand Bare Copper Element 2: 22 AWG 7 Strand Bare Copper
INSULATION	Element 1: Plenum Rated Polyvinylchloride, .066" Element 2: Foamed FEP, .068"
COLOR CODE	Element 1: Black/Red Element 2: Blue/White
LAY LENGTH	2.5" Left Hand Lay
SHIELD	Element 1: N/A Element 2: Aluminum/Mylar Tape, Foil-In, 100% Coverage
DRAIN WIRE	Element 1: N/A Element 2: 24 AWG 7 Strand Tinned Copper (Inside Foil)
JACKET	Plenum Rated Polyvinylchloride
JACKET COLOR	Black Jacket
MARKING	SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 E143242-L 18AWG 2C + 22AWG 1PR SHIELDED DATA 75C (UL) CL3P OR C(UL)US CMP FT6 ROHS COMPLIANT MADE IN USA
OVERALL DIAMETER	.190"
CABLE WEIGHT	30 lbs./mft.
CAPACITANCE	12.8 pF/ft.
IMPEDANCE	102 Ohms
DC RESISTANCE	16.6 Ohms/mft. @ 20 C
VOLTAGE RATING	300V

INDUSTRY STANDARDS

FLAME RATING	NFPA 262
AGENCY APPROVALS	NEC (NFPA 70) articles 800, 725, and 760; Section 60 of CEC, Part 1; C(UL)US listed as CMP per UL standard 444 and CSA C22.2 No. 214-17; UL listed as CL3P per UL standard 13; RoHS 2002/95/EC Directive, RoHS 2 2011/65/EU Directive, RoHS 3 2015/863/EU Directive; REACH compliant; Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.