

PART NUMBER CAT5DB-BLK

■ 0275/0725 FT ●

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable For Data Transmissions up to 100MHz. This Cable is Non-Plenum Rated and Verified to Category 5e Electricals and designed for outdoor use - UV Resistant
CONDUCTOR	24 AWG Solid Bare Copper
INSULATION	PE
COLOR CODE	White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown
JACKET	Polyethelene, Black in color; .240" Nom. Flooding compound under jacket
JACKET COLOR	Black Jacket
MARKING	A B C D E 0 1 2 3 4 5 6 7 8 9 4PR 24 AWG OUTDOOR DIRECT BURIAL CAT 5E
OVERALL DIAMETER	.232" Nom.
CABLE WEIGHT	23 Lbs/Mft.
CAPACITANCE	17 pF/ft MAX.
IMPEDANCE	100 ohms +/-15% (1-100 MHz)
TEMPERATURE RATING	-70 C to +75C / 300 Volt MAX.
VOLTAGE RATING	300 Volts

INDUSTRY STANDARDS



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.