## PART NUMBER CAT5P-BLK

ETL Listed and Rated Type CMP Multi-Pair Non-Shielded Plenum Category 5e Cable

■ 0275/0725 FT •

## A B C D E 0 1 2 3 4 5 6 7 8 9





## **CABLE SPECIFICATIONS**

**DESCRIPTION** 24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable for Data Transmission up to 350 MHz.

This cable is Plenum Rated and Verified to Category 5e Electricals

**CONDUCTOR** 24 AWG Solid Bare Copper

INSULATION FEP

**COLOR CODE** White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown

JACKET Low-Smoke PVC

JACKET COLOR Black Jacket

MARKING \* 1000/0000 \* A B C D E 0 1 2 3 4 5 6 7 8 9 UTP 4/24 C(ETL)US CMP VERIFIED (ETL) CAT5E

5013896 350 MHZ TIA-568-C.2 WINDY CITY WIRE MADE IN USA

OVERALL DIAMETER .175" Nom.

CABLE WEIGHT 24 Lbs/Mft.

**CAPACITANCE** 5.6 nF/100 Meters @ 1 kHZ

**IMPEDANCE** 100 +/- 15 Ohms (0.772-100.0 MHz)

DC RESISTANCE 9.38 Ohms / 100 Meters @ 20 C

**TEMPERATURE RATING** 60 C / 300 Volt

**VOLTAGE RATING** 300 Volts

## **INDUSTRY STANDARDS**

**FLAME RATING** Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS ETL Listed Type CMP, Verified to ANSI/TIA 568-C.2 UTP Category 5E



