PART NUMBER CAT5P-PNK-NAV-500

ETL Listed and Rated Type CMP Multi-Pair Non-Shielded Plenum Category 5e Cable

■ 0275/0725 FT •

A B C D E 0 1 2 3 4 5 6 7 8 9 VERIFIED ANSI/TIA 568-C.2 CAT 5e





CABLE SPECIFICATIONS

DESCRIPTION 24 AWG Category 5e Unshielded Twisted Pair (UTP) Cable for Data Transmission up to 350 MHz.

This cable is Plenum Rated and Verified to Category 5e Electricals

24 AWG Solid Bare Copper **CONDUCTOR**

FEP **INSULATION**

COLOR CODE White-Blue/Blue, White-Orange/Orange, White-Green/Green, White-Brown/Brown

JACKET Low-Smoke PVC

JACKET COLOR Pink Jacket

> * 1000/0000 * A B C D E 0 1 2 3 4 5 6 7 8 9 UTP 4/24 C(ETL)US CMP VERIFIED (ETL) CAT5E **MARKING**

> > 5013896 350 MHZ TIA-568-C.2 WINDY CITY WIRE MADE IN USA

OVERALL DIAMETER .175" Nom.

> **CABLE WEIGHT** 24 Lbs/Mft.

CAPACITANCE 5.6 nF/100 Meters @ 1 kHZ

IMPEDANCE 100 +/- 15 Ohms (0.772-100.0 MHz)

DC RESISTANCE 9.38 Ohms / 100 Meters @ 20 C

60 C / 300 Volt **TEMPERATURE RATING**

> **VOLTAGE RATING** 300 Volts

INDUSTRY STANDARDS

FLAME RATING Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test

AGENCY APPROVALS ETL Listed Type CMP, Verified to ANSI/TIA 568-C.2 UTP Category 5E





All specifications referenced are nominal measurements unless otherwise noted.