


PART NUMBER CAT5S-WHT

ETL Listed and Rated CMR Multi-Pair Shielded Category 5e Cable

■ 0275/0725 FT ● FTP 4/24 C(ETL)US CMR CAT 5E CHARACTERIZED TO 350 MHZ TIA-568B-C.2 WINDY CITY WIRE MADE IN THE USA



CABLE SPECIFICATIONS

DESCRIPTION	24 AWG Category 5e Shielded Four Twisted Pair, High Performance Cable for Data Transmission up to 350 MHz.
CONDUCTOR	24 AWG Solid Bare Copper
INSULATION	Polyethylene
COLOR CODE	Pair 1: Blue/White, Pair 2: Orange/White, Pair 3: Green/White, Pair 4: Brown/White
SHIELD	Aluminum Foil Shield
JACKET	PVC .020"
JACKET COLOR	White Jacket
MARKING	A B C D E 0 1 2 3 4 5 6 7 8 9 FTP 4/24 C(ETL)US CMR CAT 5E CHARACTERIZED TO 350 MHZ TIA-568B-C.2 WINDY CITY WIRE MADE IN THE USA
OVERALL DIAMETER	.242" Nom.
CAPACITANCE	17 pF/ft Nom.
IMPEDANCE	Characteristic Impedance: 100 ohms +/- 15% (1-100 MHz)
DC RESISTANCE	28.6 Ohms/1000' Max/5% Max
TEMPERATURE RATING	Installation Temperature: 0 deg. C to 60 deg. C Operation Temperature: -20 deg. C to 60 deg. C

INDUSTRY STANDARDS

AGENCY APPROVALS ETL Type CMR, C(ETL) CMR, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.