


# PART NUMBER MCF-762360

UL Listed and Rated Type FPLP / FAMC



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	18 AWG 2 Conductor Bare Copper, Non-Shielded Fire Alarm, FPLP (UL)
<b>CONDUCTOR</b>	18 (Solid Bare Copper)
<b>INSULATION</b>	Low-Smoke PVC .010"
<b>COLOR CODE</b>	Black/Red
<b>JACKET</b>	Low-Smoke PVC .018"
<b>JACKET COLOR</b>	Red Jacket
<b>MARKING</b>	FIRE/LIFE SAFETY CONTROL CABLE INIT. / IND. DEVICE / ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 18 AWG FPLP (UL) ROHS MADE IN THE USA
<b>OVERALL DIAMETER</b>	Overall MC Diameter = .525" Nom. MC Armor Material = Aluminum
<b>CABLE WEIGHT</b>	53 Lbs/Mft.
<b>CAPACITANCE</b>	22 pF/Ft. Nom.
<b>TEMPERATURE RATING</b>	0 C to 75 C / 300 Volt

## INDUSTRY STANDARDS

<b>FLAME RATING</b>	APPROVED FOR PLENUM USE WITHOUT CONDUIT PER NFPA 262 FLAME TEST
<b>AGENCY APPROVALS</b>	UL 62, 83, 910, 1424, 1479, 1569, 1581 NEC 300.22(C), 330, 430-472, 518, 530, 645, 727, 760.71(D) COMPLIES WITH FEDERAL SPECIFICATIONS A-A-59544(FORMERLY J-C-30B) NEC ARTICLE 760; FPLP (UL), ROHS COMPLIANT, MADE IN THE USA



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.