

PART NUMBER RG58-BLK

■ 0275/0725 FT ●

RG 58 A/U 20 AWG TYPE CL2 60 C (UL) E57497 OR AWM 1354



CABLE SPECIFICATIONS

DESCRIPTION	Type RG 58/U, PVC, 20 AWG Tinned Copper Center Conductor with a 95% Tinned Copper Braid, UL Listed Type CL2
CONDUCTOR	20 AWG (19/32) Tinned Copper
INSULATION	.037" Foam Polyethylene
SHIELD	95% Tinned Copper Braid
JACKET	.031" PVC 1049
JACKET COLOR	Black Jacket
MARKING	991049 RG 58 A/U 20 AWG TYPE CL2 60 C (UL) E57497 OR AWM 1354 XXXXXXXX WO# = XXXXXXX
OVERALL DIAMETER	.198" Nom
CABLE WEIGHT	26 lbs/mft.
CAPACITANCE	26 pF/ft. Nom.
IMPEDANCE	50 Ohms
TEMPERATURE RATING	60 C Max Operating

INDUSTRY STANDARDS

FLAME RATING	UL 1581 Vertical Tray Flame Test UL listed as CL2 UL recognized component AWM Style 1354
---------------------	--



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.