

PART NUMBER RG59HD-BLK

UL Listed and Rated Type CL2R or CMR

■ 0275/0725 FT ●

SMARTWIRE(TM) PRO A/V

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

DESCRIPTION	Type RG 59/U Non-Plenum, 20 AWG Solid Bare Copper Center Conductor with a 100% Bonded Aluminum Foil Shield & 95% Tinned Copper Braid, UL Listed Type CL2R/CMR
CONDUCTOR	20 AWG Solid Bare Copper
INSULATION	Foam Polyethylene
SHIELD	100% Bonded Aluminum Foil & 95% Tinned Copper Braid
JACKET	Flame Retardant PVC .032" Nom.
JACKET COLOR	Black Jacket
MARKING	SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 CL2R (UL) 20 AWG 75 C. CMR C(UL) US RoHS COMPLIANT
OVERALL DIAMETER	.234" Nom.
CABLE WEIGHT	36 Lbs/Mft.
CAPACITANCE	16.8 pF/ft. Nom.
IMPEDANCE	75 Ohms
TEMPERATURE RATING	75 C / 300 Volt

INDUSTRY STANDARDS

AGENCY APPROVALS Serial Digital Cable, Type CL2R/CMR, C(UL)



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC. All rights reserved.