

# PART NUMBER RG59HDP-WHT

UL Listed and Rated Type CL2P or CMP



## CABLE SPECIFICATIONS

<b>DESCRIPTION</b>	Type RG 59/U Plenum, 20 AWG Solid Bare Copper Center Conductor with a 100% Bonded Aluminum Foil Shield & 95% Tinned Copper Braid, HDSOI, UL Listed Type CL2P/CMP
<b>CONDUCTOR</b>	20 AWG Solid Bare Copper
<b>SHIELD</b>	100% Bonded Aluminum Foil & 95% Tinned Copper Braid
<b>JACKET</b>	Low-Smoke PVC .017" Nom.
<b>JACKET COLOR</b>	White Jacket
<b>MARKING</b>	SMARTWIRE PRO A/V A B C D E 0 1 2 3 4 5 6 7 8 9 CL2P OR CMP 20 AWG 75 C (UL) C(UL) FT-6 RG 59/U PLENUM
<b>OVERALL DIAMETER</b>	.198" Nom.
<b>CABLE WEIGHT</b>	36 Lbs/Mft.
<b>CAPACITANCE</b>	16.8 pF/ft. Nom.
<b>IMPEDANCE</b>	75 Ohms
<b>TEMPERATURE RATING</b>	75 C / 300 Volt

## INDUSTRY STANDARDS

**AGENCY APPROVALS** Serial Digital Cable, Type CL2P/CMP, C(UL)



All specifications referenced are nominal measurements unless otherwise noted.



**WINDY CITY WIRE** • T 800.379.1191 • [windycitywire.com](http://windycitywire.com)

© Windy City Wire, Cable Technology & Products, LLC.  
All rights reserved.