## PART NUMBER WCW-22/3BLU-WC

UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ● TEMPER	ATURE CONTROL SYSTEM FC BUS A B C D E 0 1 2 3 4 5 6 7 8 9
CABLE SPECIFICATIONS DESCRIPTION CONDUCTOR INSULATION COLOR CODE LAY LENGTH SHIELD DRAIN WIRE	22 AWG 3 twisted Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP 22 (7/30 Bare Copper) Low-Smoke PVC .008" Black/White/Blue 2.5" LHL (approx. 4.8 TPF) Aluminum Mylar 24 AWG 7 Strand Tinned Copper
JACKET JACKET COLOR	Low-Smoke PVC .018" Blue
MARKING	TEMPERATURE CONTROL SYSTEM FC BUS A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA
OVERALL DIAMETER	.134" Nom.
CABLE WEIGHT	15 Lbs/Mft.
CAPACITANCE	51 pF/Ft. Nom.
IMPEDANCE	37 Ohms
TEMPERATURE RATING	0 C to 75 C / 300 Volt

## **INDUSTRY STANDARDS**

FLAME RATING	Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test
AGENCY APPROVALS	NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

