

PART NUMBER WCW-22/3PUR-WC


UL Listed and Rated Type CMP Multi-Conductor Shielded Plenum Cable

■ 0275/0725 FT ●

TEMPERATURE CONTROL SYSTEM

FC BUS

A B C D E 0 1 2 3 4 5 6 7 8 9



CABLE SPECIFICATIONS

| | |
|---------------------------|--|
| DESCRIPTION | 22 AWG 3 Conductor Bare Copper, Shielded Plenum, UL Listed C(UL)US CMP |
| CONDUCTOR | 22 (7/30 Bare Copper) |
| INSULATION | Low-Smoke PVC .008" |
| COLOR CODE | Black/White/Purple |
| SHIELD | Aluminum Mylar |
| DRAIN WIRE | 24 AWG 7 Strand Tinned Copper |
| JACKET | Low-Smoke PVC .018" |
| JACKET COLOR | Purple |
| MARKING | TEMPERATURE CONTROL SYSTEM FC BUS A B C D E 0 1 2 3 4 5 6 7 8 9 22 AWG C(UL)US CMP ROHS MADE IN THE USA |
| OVERALL DIAMETER | .134" Nom. |
| CABLE WEIGHT | 15 Lbs/Mft. |
| CAPACITANCE | 51 pF/Ft. Nom. |
| IMPEDANCE | 37 Ohms |
| TEMPERATURE RATING | 0 C to 75 C / 300 Volt |

INDUSTRY STANDARDS

| | |
|-------------------------|---|
| FLAME RATING | Approved For Plenum Use Without Conduit Per NFPA 262 Flame Test |
| AGENCY APPROVALS | NEC Article 800; UL Listed C(UL)US CMP, RoHS Compliant, Made in the USA |



All specifications referenced are nominal measurements unless otherwise noted.



WINDY CITY WIRE • T 800.379.1191 • windycitywire.com

© Windy City Wire, Cable Technology & Products, LLC.
All rights reserved.