PART NUMBER 413106

UL Listed and Rated Type CMR Multi-Conductor Shielded Non-Plenum Cable

■ 0275/0725 FT ●	SMARTWIRE(TM) DEVICE/ZONE	A B C D E 0 1 2 3 4 5 1	6789	SMARTWIRE GLIDE
		,			TECHNOLOGY
CABLE SPECIFICA	TIONS				
DESCRIPTION		16 AWG 2 Conductor Bare Copper, Shielded Non-Plenum, UL Listed C(UL)US CMR			
CONE	DUCTOR 1	R 16 (19/29 Bare Copper)			
INSU	LATION P	VC .008"			
COLO	R CODE B	lack/White	1.1		
LAY I	LENGTH 3	.5" LHL (approx. 3.4 TPF)	11. A.		
:	SHIELD A	luminum Mylar			
DRAI	N WIRE 2	2 AWG 7 Strand Tinned Co	pper		
	JACKET P	VC .018"			
JACKET	COLOR	Gray Jacket with Green Stri	ре		
MA		MARTWIRE DEVICE / ZONE N THE USA	A B C D E 0 1 2 3 4 5	6789 16 AWG	G C(UL)US CMR 75C MADE
OVERALL DIA	AMETER .1	.84" Nom.			
CABLE V	WEIGHT 34	4 Lbs/Mft.			R
CAPAC	ITANCE 7	6 pF/Ft. Nom.			
IMPE	EDANCE 2	5 Ohms			
TEMPERATURE I	RATING) C to 75 C / 300 Volt			

INDUSTRY STANDARDS

AGENCY APPROVALS

NEC Article 800; UL Listed C(UL)US CMR, RoHS Compliant, Made in the USA



All specifications referenced are nominal measurements unless otherwise noted.

WINDY CITY WIRE · T 800.379.1191 · windycitywire.com · [©] Windy City Wire, Cable Technology & Products, LLC. All rights reserved.